ALTMAN

Catalog number: SKY-CYC-01 SKY-CYC-02H SKY-CYC-02V

SKY-CYC-03 SKY-CYC-04

**1500 Watts** 

# SKY-CYC

A lightweight, wide spread, luminaire designed to provide an even wash of light on cycloramas; the four light sky cyc, when mounted 8 feet from the cyc, 12 feet on center will typically provide better than 1.3 to 1 uniformity between luminaires with a minimum of 176 footcandles at the bottom of a 20' cyc. Available in many configurations, the SKY-CYC is ideally suited for use in theatres and television studios as a compact, lightweight means of lighting large cycloramas from above.

#### **Features**

- Lightweight
- Wide spacing 12' O.C. typical
- Broad even distribution
- High efficiency reflector
- Multiple mounting configurations
- Safety screen(s) included
- U.L. and c.U.L. listed for 1500 watts

Specifications may vary from time of printing.

SKY-CYC-01

SKY-CYC-02V


Hanging Weight - Approx. 12 lbs. (5.4 kg)

Hanging Weight - Approx. 37 lbs. (16.8 kg)

SKY-CYC-03

SKY-CYC-03

(132 cm)





Hanging Weight - Approx. 52 lbs. (23.6 kg)



Altman Stage Lighting Company, Inc. 57 Alexander Street, Yonkers, NY 10701

914-476-7987

212-569-7777

FAX: 914-963-7304

Catalog number: SKY-CYC-01 SKY-CYC-02H SKY-CYC-02V

SKY-CYC-03 SKY-CYC-04

## **Specifications**

**HOUSING**: Sheet aluminum and die-cast aluminum construction.

**MATERIALS:** Construction employs all corrosion-resistant hardware.

**RATING:** 120 volts AC/DC operation, 12.5/6.25 amps, 1500 watts maximum per section.

**SOCKET:** Recessed single contact, two provided

per section. Tooless relamping.

**CABLE:** 36" Teflon leads encased in black fiberglass sleeving, one set of leads provided per section.

YOKE: 1/8" x 2" extruded aluminum channel

with dual handles.

GANGING IRONS: Rigid flat steel with

four handles.

**REFLECTOR:** Peened specular aluminum. **FINISH:** Baked black enamel, electrostatic application.

SAFETY SCREEN: Stainless Steel, one provided

with each section.

**WEIGHT:** Approx. 12 lbs. for SKY-CYC-01, approx. 22 lbs. SKY-CYC-02H, approx. 37 lbs. for SKY-CYC-02V, approx. 28 lbs. for SKY-CYC-03, and approx. 52 lbs. for SKY-CYC-04.

### **Accessories**

#### Supplied with luminaire

510 Malleable Iron Pipe Clamp

with 1 & 2 section units

510-HD Heavy Duty Malleable Iron

Pipe Clamp with 3 & 4


section units

SC Safety Cable with

Spring Clip

#### **Additional Accessories**

SC-CF Color Frame



| SKY-CYC PERFORMANCE CHART WITH FDB LAMP |                          |                                |                                 |                   |  |  |  |  |
|---|--------------------------|--------------------------------|---------------------------------|-------------------|--|--|--|--|
| Fixture<br>Type                         | Candlepower<br>(Candela) | Beam Angle<br>(Degrees)<br>H V | Field Angle<br>(Degrees)<br>H V | Efficiency<br>(%) |  |  |  |  |
| SKY-CYC-01                              | 10,924                   | 100° x 105°                    | 108° x 107°                     | 62.4              |  |  |  |  |

| LAMP DATA |              |        |                    |        |       |                    |                      |  |  |
|-----------|--------------|--------|--------------------|--------|-------|--------------------|----------------------|--|--|
| Watts     | ANSI<br>Code | Finish | Color<br>Temp (°K) | Lumens | Volts | Rated Life (Hours) | Correction<br>Factor |  |  |
| 1500      | FDB          | Clear  | 3200               | 41,200 | 120   | 400                | 1.0                  |  |  |
| 1500      | FGT          | Frost  | 3200               | 40,200 | 120   | 400                | _                    |  |  |
| 1000      | FFT          | Clear  | 3200               | 26,400 | 120   | 400                | .64                  |  |  |
| 1000      | FGV          | Frost  | 3200               | 25,700 | 120   | 400                | _                    |  |  |



Altman Stage Lighting Company, Inc.

57 Alexander Street, Yonkers, NY 10701

914-476-7987

212-569-7777

FAX: 914-963-7304